

Location: _____



R1300T

SCUPPER DRAIN WITH ANGLE GRATE AND 90 DEGREE THREADED OUTLET

Specification: MIFAB R1300T lacquered cast iron scupper drain with 90 degree threaded outlet, membrane clamp and sloped grate (specify cast iron (Suffix -50) or nickel bronze (Suffix -1)).

Function: To provide drainage from a roof surface horizontally where the roof and parapet meet. The angled grate prevents debris from blocking the drainage openings. Reverse outlet for 45 degree outlet connection (R1310).

45 DEGREE SLOPED GRATE WITH 27 IN² OF FREE AREA (57in² OF FREE AREA WITH 6" and 8" MODELS)

2", 3", 4", 6" OR 8" (51, 76, 102, 152, 203) STANDARD THREADED 90 DEGREE OUTLET

HS-1 HARDWARE

MEMBRANE CLAMP

PIPE SIZE

MODEL NUMBER	A	B	C
R1302,3,4T	7 1/2 [191]	6 3/8 [162]	2 3/4 [70]
R1306,8T	12 1/2 [318]	8 3/8 [213]	3 1/2 [89]

(Dimension) Denotes Millimetres

R1300 Series Meets ASME Roof Drain Standard A112.6.4-2003

SUFFIX OPTIONAL VARIATIONS

- 1 Nickel bronze frame and grate
- 6 Vandal proof grate
- 11 Acid resistant epoxy finish
- 13 All galvanized
- 50 Cast iron frame and grate
- 83 Stainless steel mesh screen over grate

SUFFIX OPTIONAL VARIATIONS

- (Standard) Threaded outlet (2", 3", 4", 6", or 8")
- NH No Hub Outlet (2", 3", 4", 6" or 8")
- BA Buy American Act compliant product
- PA Pennsylvania Steel Act compliant product

Job Name: _____
 Section No: _____
 Schedule No: _____

Page No: _____
 Contract: _____
 Purchase Order No: _____